



MODEL	TRAVEL	RETR	EXTD	STL WGT	STL HP
OV20-01	12.00	38.00	50.00	494 LB	C/F
OV20-02	24.00	40.00	64.00	518 LB	C/F
OV20-03	36.00	42.00	78.00	536 LB	C/F
OV20-04	48.00	46.00	94.00	565 LB	C/F
OV20-05	60.00	48.00	108.00	582 LB	C/F
OV20-06	72.00	52.00	124.00	612 LB	C/F
OV20-07	84.00	54.00	138.00	630 LB	C/F
OV20-08	96.00	58.00	154.00	659 LB	C/F
OV20-09	108.00	60.00	168.00	675 LB	C/F

GENERAL NOTES:

LOADING CAPACITY: 120 CFM
AVERAGE AIR WITHDRAWAL: 450 CFM
LIFTING SPEED: 16 FPM AVG

ALL INDUSTRIAL VOLTAGES ARE AVAILABLE FOR ELECTRICAL COMPONENTS.

PREWIRING OF ELECTRICAL COMPONENTS TO SPOUT FRAME JUNCTION BOX OPTIONAL.

ELECTRICAL ENCLOSURES NEMA 4 STANDARD. NEMA 4X, 7, AND 9 OPTIONAL.

COLLAPSIBLE FABRIC SLEEVE CAN BE CONSTRUCTED OF URETHANE/NYLON, HYPALON/NYLON, OR A NUMBER OF OTHER FABRICS. SLEEVES COME STANDARD WITH ALUMINUM OUTER AND INNER RINGS STANDARD.

METAL SURFACES ARE POWER TOOL CLEANED, PRIMED, AND FINISHED WITH INDUSTRIAL ENAMEL.

LOADING CAPACITY LISTED IS APPROXIMATE AND BASED ON FREE FLOWING PRODUCTS. CONSULT DCL FOR ACTUAL REQUIREMENTS.

AIR WITHDRAWAL REQUIREMENTS ARE AVERAGE. CONSULT DCL FOR FINAL RECOMMENDATIONS.

SPECIFICATIONS AND/OR DIMENSIONAL DATA ARE SUBJECT TO CHANGE. CONSULT DCL FOR CERTIFIED DRAWINGS.

CONE CONSTRUCTION NOTES: CONTAINED INNER DESIGN STANDARD WITH 0.13 AR STEEL, AND 0.13 304 OR 316 STAINLESS STEEL. OTHER MATERIALS AVAILABLE TO SUIT APPLICATION.

OPTIONS:

150# INLET FLANGE. ADDS 3.00 TO RETRACTED HEIGHT.

LEVEL SENSORS; TILT PROBE, RF PROBE, CAPACITANCE PROBE, PNEUMATIC PROBE.

AIR VIBRATOR KIT REQUIRES (40) CFM @ (80) PSI.

*ESTIMATED WEIGHTS DO NOT INCLUDE OPTIONAL EQUIPMENT OR ELECTRICAL COMPONENTS.

REV	DATE	BY	DCL		P.O. BOX 125
			SPECIALISTS IN ADVANCED DESIGN LOADING SYSTEMS		CHARLEVOIX, MICHIGAN 49720 (231) 547-5600
			TOLERANCES UNLESS OTHERWISE SPECIFIED		DRAWN BY: JNM SCALE: NONE
			FRACTIONAL: 1/16"	DECIMAL: .06	CHECKED BY: ENG DATE: 10-02-00
					ANGULAR: 1/2"
A	08-07-02	JNM	TITLE: OV20 LOADING SPOUT (OV STYLE)		DRAWING No: OV20-10001